

(19) World Intellectual Property Organization
International Bureau



10/517946



(43) International Publication Date
24 December 2003 (24.12.2003)

PCT


(10) International Publication Number
WO 03/107087 A1

- (51) International Patent Classification⁷: G02F 1/37, G02B 27/00 // 5/00
- (74) Agent: TAMPEREEN PATENTTITOIMISTO OY; Hermiankatu 12 B, FIN-33720 Tampere (FI).
- (21) International Application Number: PCT/FI02/00512
- (81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 13 June 2002 (13.06.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (*for all designated States except US*): NOKIA CORPORATION [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).
- (72) Inventor; and
- (73) Inventor/Applicant (*for US only*): SCHORPP, Marcus [DE/FI]; Vaunukatu 35 A 2, FIN-33730 Tampere (FI).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent

[Continued on next page]

(54) Title: ENHANCEMENT ELECTRODE CONFIGURATION FOR ELECTRICALLY CONTROLLED LIGHT MODULATORS

"ON"



(57) Abstract: An electrically controlled light modulator device comprises at least one cell, where two deformable dielectric layers (12,13) meet at an interface, at least one of said layers consisting of viscoelastic relief forming gel (12). A first support electrode structure (14) and a second signal electrode structure (10) are arranged on separate sides of the dielectric layers (12,13) in order to create an electric field passing through said layers (12,13) and in order to create surface reliefs on the viscoelastic gel layer (12). According to the invention, a third enhancement electrode structure (40,50) is arranged in the proximity of the first signal electrode structure (10). Applying enhancement signal voltage between the enhancement electrode structure (40,50) and the signal electrode structure (10) concentrates locally the electric field passing through the two deformable dielectric layers (12,13) and therefore enhances the amplitude of the deformation of the viscoelastic gel layer (12).



(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report